

```

/*
 * interrupt_counter_tut_2B.c
 *
 * Created on: Unknown
 * Author: Ross Elliot
 * Version: 1.1
 */

/*****

* VERSION HISTORY
*****
* v1.1 - 01/05/2015
* Updated for Zybo ~ DN
*
* v1.0 - Unknown
* First version created.
*****/

#include "xparameters.h"
#include "xgpio.h"
#include "xtmrctr.h"
#include "xscugic.h"
#include "xil_exception.h"
#include "xil_printf.h"

// Parameter definitions
#define INTC_DEVICE_ID XPAR_PS7_SCUGIC_0_DEVICE_ID
#define TMR_DEVICE_ID XPAR_TMRCTR_0_DEVICE_ID
#define BTNS_DEVICE_ID XPAR_AXI_GPIO_0_DEVICE_ID
#define LEDS_DEVICE_ID XPAR_AXI_GPIO_1_DEVICE_ID
#define INTC_GPIO_INTERRUPT_ID XPAR_FABRIC_AXI_GPIO_0_IP2INTC_IRPT_INTR
#define INTC_TMR_INTERRUPT_ID XPAR_FABRIC_AXI_TIMER_0_INTERRUPT_INTR

#define BTN_INT XGPIO_IR_CH1_MASK
#define TMR_LOAD 0xF8000000

XGpio LEDInst, BTNInst;

```

```

XScuGic INTCInst;
XTmrCtr TMRInst;
static int led_data;
static int btn_value;
static int tmr_count;

//-----
// PROTOTYPE FUNCTIONS
//-----
static void BTN_Intr_Handler(void *baseaddr_p);
static void TMR_Intr_Handler(void *baseaddr_p);
static int InterruptSystemSetup(XScuGic *XScuGicInstancePtr);
static int IntcInitFunction(u16 DeviceId, XTmrCtr *TmrInstancePtr, XGpio *GpioInstancePtr);

//-----
// INTERRUPT HANDLER FUNCTIONS
// - called by the timer, button interrupt, performs
// - LED flashing
//-----

void BTN_Intr_Handler(void *InstancePtr)
{
    // Disable GPIO interrupts
    XGpio_InterruptDisable(&BTNInst, BTN_INT);
    // Ignore additional button presses
    if ((XGpio_InterruptGetStatus(&BTNInst) & BTN_INT) !=
        BTN_INT) {
        return;
    }
    btn_value = XGpio_DiscreteRead(&BTNInst, 1);
    // Increment counter based on button value
    // Reset if centre button pressed
    led_data = led_data + btn_value;

    XGpio_DiscreteWrite(&LEDInst, 1, led_data);
    (void)XGpio_InterruptClear(&BTNInst, BTN_INT);
    // Enable GPIO interrupts

```

```

    XGpio_InterruptEnable(&BTNInst, BTN_INT);
}

void TMR_Intr_Handler(void *data)
{
    if (XTmrCtr_IsExpired(&TMRInst,0)){
        // Once timer has expired 3 times, stop, increment counter
        // reset timer and start running again
        if(tmr_count == 3){
            XTmrCtr_Stop(&TMRInst,0);
            tmr_count = 0;
            led_data++;
            XGpio_DiscreteWrite(&LEDInst, 1, led_data);
            XTmrCtr_Reset(&TMRInst,0);
            XTmrCtr_Start(&TMRInst,0);

        }
        else tmr_count++;
    }
}

```

```

//-----
// MAIN FUNCTION
//-----
int main (void)
{
    int status;
    //-----
    // INITIALIZE THE PERIPHERALS & SET DIRECTIONS OF GPIO
    //-----
    // Initialise LEDs
    status = XGpio_Initialize(&LEDInst, LEDS_DEVICE_ID);
    if(status != XST_SUCCESS) return XST_FAILURE;
    // Initialise Push Buttons
    status = XGpio_Initialize(&BTNInst, BTNS_DEVICE_ID);
    if(status != XST_SUCCESS) return XST_FAILURE;
}

```

```

// Set LEDs direction to outputs
XGpio_SetDataDirection(&LEDInst, 1, 0x00);
// Set all buttons direction to inputs
XGpio_SetDataDirection(&BTNInst, 1, 0xFF);

//-----
// SETUP THE TIMER
//-----
status = XTmrCtr_Initialize(&TMRInst, TMR_DEVICE_ID);
if(status != XST_SUCCESS) return XST_FAILURE;
XTmrCtr_SetHandler(&TMRInst, TMR_Intr_Handler, &TMRInst);
XTmrCtr_SetResetValue(&TMRInst, 0, TMR_LOAD);
XTmrCtr_SetOptions(&TMRInst, 0, XTC_INT_MODE_OPTION | XTC_AUTO_RELOAD_OPTION);

// Initialize interrupt controller
status = IntcInitFunction(INTC_DEVICE_ID, &TMRInst, &BTNInst);
if(status != XST_SUCCESS) return XST_FAILURE;

XTmrCtr_Start(&TMRInst, 0);

while(1);

return 0;
}

//-----
// INITIAL SETUP FUNCTIONS
//-----

int InterruptSystemSetup(XScuGic *XScuGicInstancePtr)
{
    // Enable interrupt
    XGpio_InterruptEnable(&BTNInst, BTN_INT);

```

```

XGpio_InterruptGlobalEnable(&BTNInst);

Xil_ExceptionRegisterHandler(XIL_EXCEPTION_ID_INT,
                             (Xil_ExceptionHandler)XScuGic_InterruptHandler,
                             XScuGicInstancePtr);

Xil_ExceptionEnable();

return XST_SUCCESS;

}

int IntcInitFunction(u16 DeviceId, XTmrCtr *TmrInstancePtr, XGpio *GpioInstancePtr)
{
    XScuGic_Config *IntcConfig;
    int status;

    // Interrupt controller initialisation
    IntcConfig = XScuGic_LookupConfig(DeviceId);
    status = XScuGic_CfgInitialize(&INTCInst, IntcConfig, IntcConfig->CpuBaseAddress);
    if(status != XST_SUCCESS) return XST_FAILURE;

    // Call to interrupt setup
    status = InterruptSystemSetup(&INTCInst);
    if(status != XST_SUCCESS) return XST_FAILURE;

    // Connect GPIO interrupt to handler
    status = XScuGic_Connect(&INTCInst,
                            INTC_GPIO_INTERRUPT_ID,
                            (Xil_ExceptionHandler)BTN_Intr_Handler,
                            (void *)GpioInstancePtr);
    if(status != XST_SUCCESS) return XST_FAILURE;

    // Connect timer interrupt to handler
    status = XScuGic_Connect(&INTCInst,
                            INTC_TMR_INTERRUPT_ID,
                            (Xil_ExceptionHandler)TMR_Intr_Handler,

```

```
                                (void *)TmrInstancePtr);
if(status != XST_SUCCESS) return XST_FAILURE;

// Enable GPIO interrupts interrupt
XGpio_InterruptEnable(GpioInstancePtr, 1);
XGpio_InterruptGlobalEnable(GpioInstancePtr);

// Enable GPIO and timer interrupts in the controller
XScuGic_Enable(&INTCInst, INTC_GPIO_INTERRUPT_ID);

XScuGic_Enable(&INTCInst, INTC_TMR_INTERRUPT_ID);

return XST_SUCCESS;
}
```